




ESSENTIAL SERIES

Project _____
Item _____
Quantity _____
CSI - 11400 _____
Approval _____
Date _____

POWER LOADER AND UNLOADER

- Labor and space saving
- Dishroom operates at peak efficiency
- May be used independently or in combination with each other
- Unique design allows for use around columns and in difficult areas
- Eliminates cumbersome, space consuming curved rollers
- Can add several feet of work space at the clean end by utilizing an additional wall
- Innovative design gives flexibility of right-to-left or left-to-right application
- Can be loaded or unloaded at a 90° angle
- Adaptable to all Insinger rack conveyor dishwashers
- Can give you the option of using a small rack conveyor instead of a single tank corner style machine
- Optional limit switch at end of clean table shuts down conveyor when clean racks accumulate




STANDARD FEATURES

- Dedicated motor, independent of the warewasher


OPTIONS

- Limit switch





POWER LOADER AND UNLOADER



SPECIFICATIONS

CAPACITY- Capacity varies with the size of the dishwasher used. Maximum capacity is 330 20" x 20" racks per hour. Will accommodate 22" long trays in an open end rack.

DESIGN- Can be used in both right-to-left and left-to-right operations. Loader and Unloader can each be used independently or in combination with each other.

CONSTRUCTION- Pan constructed of 16 gauge type 304 18-8 stainless steel with all welded construction. Both Loader and Unloader are furnished with a 10" back-splash and a 1 1/2" rim roll. All moving parts with the exception of the pusher and rollers are covered with a stainless steel panel.

OPERATION-

Power Loader- 3 powered rollers with an operating speed of 10 surface feet per minute. Rollers powered by a chain drive operated by a 1/3 hp motor and reduction gear combination.

Power Unloader- 3 powered rollers with an operating speed of 10 surface feet per minute plus a simultaneously timed rack ejector. Rollers powered by a chain drive operated by a 1/15 hp motor. Ejector powered by a 1/4 hp motor through a reduction gear and sprockets protected by a safety clutch to deliver a stroke of 15-20 feet per minute. Stroke is fast enough to push the clean dish rack out and reposition the ejector to receive the next rack as it exits the dishwasher.

MOTORS- 1/3 hp motor furnished with Power Loader. 1/4 hp and 1/5 hp motors furnished with Power Unloader. Motors are standard frame, internally fan-cooled with ball bearing construction.

DRAIN- Drain for Unloader is connected to machine.

Contact Insinger Sales at 800-344-4802 for an installation drawing specific to your application.
This drawing is available on the Insinger website at www.insingermachine.com

Note: Due to product improvement we reserve the right to change information and specifications without notice.

